


Data Sheet

Item	Contents		Criteria (Adjustable)
1	Model	SD098	3S-5A working current
2	Voltage	Charging voltage	12.6V
3	Current	Maximal continuous charging current	5A
		Maximal continuous discharging current	5A
		Current consumption	≤50μA
4	Overcharge Protection	Over charge detection voltage	4.28V±0.025V
		Over charge detection delay time	0.5~2S
		Over charge release voltage	4.08V±0.05V
5	Over Discharge Protection	Over discharge detection voltage	3.00V±0.05V
		Over discharge detection delay time	50~200mS
		Over discharge release voltage	3.00V±0.1V
6	Over Current Protection	Over current detection voltage	0.1V~0.2V
		Over current detection current	10A±2A
		Detection delay time	5~20mS
		Release condition	Cut load,automatically recover
7	Short Circuit Protection	Detection condition	Exterior shot circuit
		Detection delay time	200~500uS
		Release condition	Cut load,automatically recover
8	Balance	Balance voltage for single cell	4.2V±0.025V
		Balance current for single cell	42±5mA
9	Resistance	Inner resistance	≤20mΩ
10	Temperature	Operating temperature range	0 ~ +85°C
		Storage temperature range	0 ~ +85°C
11	Size (L*W*T)	L64mm*W54mm*T8mm	

Remarks:



Temperature sensor: 60° C

Charge, Discharge at same Port
 P+=B+/Charge+ /Discharge+
 P-=Charge- /Discharge-

*Note: Characteristics subject to change without notice.